

SUPROL PRO

Description

SUPROL PRO is a ready-for-use, waterless solution for the rinsing of disassembled and assembled clockworks after the cleaning in watch cleaning machines. The cleaning solution used before is thoroughly removed and **SUPROL PRO** evaporates without residue. Subsequent lubricants will be taken uniform by the rinsed surfaces.

SUPROL PRO is also suitable for rinsing and water replacement before the drying in the course of an aqueous cleaning and rinsing process for metallic precision parts. **SUPROL PRO** does not contain benzene and it is dearomatized.

Application and Dosage

- Dosage: pure, ready-for-use • Rinsing time: about 3 min.
- If one of the Elma cleaning machines Elmasolvex VA, RM and SE as well as RM 90 or Superelite is used, at first clean the clockworks in WF PRO.
- Then rinse multiple with the rinsing solution **SUPROL PRO**.
- If a complete re-lubrication is required, use UNIMIX for the last rinsing step.

Safety Recommendations

SUPROL PRO is classified as hazardous according to the Regulation (EC) No 1272/2008 [GHS] (flammable, eye irritation, narcotic effect, aspiration toxicity, hazardous to the aquatic environment - chronic category 3).

Observe also with respect to this the hints indicated in the safety data sheet and always handle chemicals with care.

Physical-chemical characterisation

- Density: 0.74-0.77 g/ml.
- Flash point: 23-28 °C.
- **SUPROL PRO** is not miscible with water and keeps on top of water.
- Mixture of solvents, free of halogens like chlorine or fluorine.

Disposal

Recommendation:

1. Disposal regulations same as for used oil/diesel/benzine.
2. Dispose via specialised disposal companies: European waste code: 14 06 03*, „other solvents and solvent mixtures“.
3. Burn in suitable equipments, but according to official regulations.

Transport in appropriate suitable containers. Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Do not discharge product unmonitored into the environment.

Volumes, Storage and Transport

- Available volumes: 2.5 l can [REF 8000440](#), 5 l can [REF 8000444](#), 10 l can [REF 8000441](#) and 30 l can [REF 8000443](#).
- Keep in tightly closed original container at a cool and ventilated place and protected from heat and direct solar radiation. Do not store together with oxidizing agents.
- Do not mix with other chemicals.
- Keep away from ignition sources.
- Shelf life: 3 years from date of production (see lot on label).
- Classification for all means of transport: class 3, UN 3295.

Accessories

- Tap (outlet tap): for 2.5 l / 5 l / 10 l / 25 l can [REF 8000003928](#).
- Dosing cup: 250 ml vol./5 ml-scale [REF 8000643](#) • 1000 ml vol./10 ml-scale [REF 8000647](#).