

## UNIMIX

### Description

**UNIMIX** is a ready-for-use, waterfree solution for lubrication of complete watches after the cleaning and a singular rinsing process, e.g. by vibration. **UNIMIX** is also suitable as relubricating rinsing solution after the cleaning and drying of metal precision parts.

### Application and Dosage

- Dosage: ready-for-use • Resting time: approx. 3 min.
- After the cleaning of the watch work with WF PRO and the subsequent rinsing with SUPROL PRO, the complete watch work is relubricated with **UNIMIX** in the third bath. If no relubrication is required, use also SUPROL PRO for the second rinsing bath.
- Shake well before use!

### Safety Recommendations

**UNIMIX** is classified as hazardous according to the Regulation (EC) No 1272/2008 [GHS] (flammable, eye irritation, narcotic effect, aspiration toxicity, hazardous to the aquatic environment - chronic category 3).

Observe also with respect to this the hints indicated in the safety data sheet and always handle chemicals with care.

### Physical-chemical characterisation

- Density: 0.69 - 0.83 g/ml.
- Flash point: 23-25°C.
- The product is not miscible with water and keeps on top of water.
- Mixture of solvents free of halogens like chlorine or fluorine with small additions of different oils.

### Disposal

Recommendation:

1. Disposal regulations same as for used oil/diesel/benzine.
2. Dispose via specialised disposal companies: European waste code: 14 06 03\*, „other solvents and solvent mixtures“.
3. Burn in suitable equipments, but according to official regulations.

Transport in appropriate suitable containers.

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Do not discharge product unmonitored into the environment.

### Volumes, Storage and Transport

- Available volumes: 1 l [REF 5801200000](#), 2.5 l [REF 5801300000](#), 5 l [REF 5801400000](#) and 10 l [REF 5801500000](#).
- Keep in tightly closed original container at a dry, cool and ventilated place and protected from heat and direct solar radiation. Do not store together with oxidizing agents. Do not mix with other chemicals. Keep away from ignition sources.
- Shelf life: 3 years from date of production (see lot on label).
- Classification for all means of transport: class 3, UN 3295.

### Accessories

- Tap (outlet tap): for 5 / 10 l cans [REF 8000003927](#) • for 25 l can [REF 8000003928](#).
- Dosing cup: 250 ml vol./5 ml-scale [REF 8000643](#) • 1000 ml vol./10 ml-scale [REF 8000647](#).